





Test Report SL52115295849201TX Date:August 24,2021 Page 1 of 10

10A LIMITED

RMS 1001-1005, 10/F, NANYANG PLAZA, 57 HUNG TO RD., KWUN TONG, KLN, HONG KONG

The following sample(s) was/were submitted and identified on behalf of the client as:

Sample Description : (A)10A NanoGo Face Mask Lotus Plus P402

Claimed : FFP2

Sample Color : (A)White

Style No. : FM3D-M-LOT-P402

Factory : 10A LIMITED Country of Origin : HONG KONG

Test Performed : Selected test(s) as requested by applicant

Sample Receiving Date : Aug 09, 2021

Testing Period : Aug 09, 2021 - Aug 24, 2021

Test Result(s) : Unless otherwise stated the results shown in this test report refer only to the

sample(s) tested, for further details, please refer to the following page(s).

Conclusion:

Sample No.	Recommendation Level
(A)	FFP2 NR

Signed for and on behalf of

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd Testing Center

Sara Guo (Account Executive)

SGS does not verify authenticity of any Brand/Trademark of products. Buyers must check if the product is genuine with the Brand/Trademark owner directly.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.
Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate so transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国·上海·徐汇区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52115295849201TX

Date: August 24,2021

Page 2 of 10

Test Result

Personal Protective Equipment - Respiratory Protective Devices- Filtering Half Masks to Protect against Particles- Requirements, Testing, Marking

EN 149:2001+A1:2009

Clause 7.4 Packaging

(EN 149:2001+A1:2009 Clause 8.2)

Test Requirement	Results	Comment
Particle filtering half masks shall be offered for sale packaged in such a way that they are protected against mechanical damage and contamination before use.	Comply	Pass

Clause 7.5 Material

(EN 149:2001+A1:2009, Clause 8.2 & 8.3.1 & 8.3.2)

Test Requirement	Results	Comment
Materials used shall be suitable to withstand handling and wear over the period for which the particle filtering half mask is designed to be used.	Comply	
After undergoing the conditioning described in 8.3.1 none of the particle filtering half masks shall have suffered mechanical failure of the facepiece or straps.	Comply	Pass
When conditioned in accordance with 8.3.1 and 8.3.2 the particle filtering half mask shall not collapse.	Comply	
Any material from the filter media released by the air flow through the filter shall not constitute a hazard or nuisance for the wearer.	Comply	

Clause 7.6 Cleaning and Disinfecting

(EN 149:2001+A1:2009, Clause 8.4 & 8.5 & 8.11)

Test Requirement	Results	Comment
If the particle filtering half mask is designed to be re-usable, the materials used shall withstand the cleaning and disinfecting agents and procedures to be specified by the manufacturer. With reference to 7.9.2, after cleaning and disinfecting the re-usable particle filtering half mask shall satisfy the penetration requirement of the relevant class.	Not applicable (Not designed to be re-usable)	N.A.

Clause 7.7 Practical Performance

(EN 149:2001+A1:2009, Clause 8.4)

Test Requirement	Results	Comment
The particle filtering half mask shall undergo practical performance tests under realistic conditions. These general tests serve the purpose of checking the equipment for imperfections that cannot be determined by the tests described elsewhere in this standard.	No imperfections	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rd Building, No. 889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52115295849201TX

Date: August 24,2021

Page 3 of 10

Clause 7.8 Finish of Parts

(EN 149:2001+A1:2009, Clause 8.2)

Test Requirement	Results	Comment
Parts of the device likely to come into contact with the wearer shall have no sharp edges or burrs.	No sharp edges or burrs	Pass

Clause 7.9.1 Total Inward Leakage

(EN 149:2001+A1:2009, Clause 8.5)

Test Requirement	Results	Comment
The total inward leakage consists of three components: face seal leakage, exhalation valve leakage (if exhalation valve fitted) and filter penetration. For particle filtering half masks fitted in accordance with the manufacturer's information, at least 46 out of the 50 individual exercise results (i.e. 10 subjects x 5 exercises) for total inward leakage shall be not greater than: 25% for FFP1, 11% for FFP2, 5% for FFP3 and, in addition, at least 8 out of the 10 individual wearer arithmetic means for the total inward leakage shall be not greater than: 22% for FFP1, 8% for FFP2, 2% for FFP3	Detail refer to Appendix 1	Meet FFP1, Meet FFP2

Appendix 1: Summarization of Test Data

Inward Leakage Test Data

inward Leakage Test Data								
Subject	Sample	Condition	Walk(%)	Head	Head	Talk(%)	Walk(%)	Mean(%)
	No.			Side/side(%)	up/down(%)			
Zhou	1	A.R.	3.71	2.81	3.43	3.89	3.03	3.37
Luo	2	A.R.	4.21	3.65	4.24	4.84	4.12	4.21
Lu	3	A.R.	3.49	3.54	3.28	3.63	3.30	3.45
Wang	4	A.R.	1.72	2.56	2.36	2.69	2.22	2.31
Bao	5	A.R.	4.10	4.30	4.48	4.88	3.92	4.34
Ding	6	T.C.	1.91	2.67	2.66	2.79	2.01	2.41
Li	7	T.C.	4.01	4.90	4.64	5.11	4.52	4.64
Chen	8	T.C.	2.33	2.99	2.38	2.97	2.48	2.63
Song	9	T.C.	3.08	3.27	3.59	4.28	3.69	3.58
Ye	10	T.C.	4.48	4.81	4.19	5.31	4.79	4.72

Facial Dimension

Subject	Face length	Face Width	Face Depth	Mouth Width
Chen	125	150	120	58
Lu	115	132	107	48
Zhou	115	135	106	52
Li	125	130	107	46
Luo	125	136	100	43
Zheng	128	140	112	55
Wang	120	147	103	48
Song	120	140	100	50
Bao	130	134	104	50



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rd Building, No. 889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



Test Report SL5211		5295849201TX	Date:August 24,202	1 Page 4 of 10
Ding	134	150	110	52
Liu	120	135	117	50
Ye	126	137	105	52

Note: A panel of ten clean-shaven persons (without beards or sideburns) were selected covering the spectrum of facial characteristics of typical users of the filtering half masks submitted by applicant (excluding significant abnormalities). It is to be expected that exceptionally some persons cannot be satisfactorily fitted with a particle filtering half mask. Such exceptional subjects shall not be used for testing particle filtering half masks.

Clause 7.9.2 Penetration of Filter Material

(EN 149:2001+A1:2009, Clause 8.11 & EN 13274-7:2019)

	Test Requirement		Results	Comment	
	of the filter of the particle filter the following table.	е			
Classifica	Maximum penetration	on of test aerosol			
tion	Sodium chloride test 95	Paraffin oil test 95 l/min			
	l/min			Detail refer to	Meet FFP1,
	%	%		Appendix 2	Meet FFP2
	max.	max.			
FFP1	20	20			
FFP2	6	6			
FFP3	1	1			

Appendix 2: Summarization of Test Data

Penetration of filter material

Aerosol	Aerosol Condition		Penetration (%)		
	Department to at	1	0.244		
	Penetration test	2	0.234		
	(As received)	3	0.265		
	Denotration toot	4	0.257		
Sodium chloride test	Penetration test (Simulated wearing treatment)	5	0.269		
	(Simulated wearing treatment)	6	0.301		
	Exposure test	7	0.475		
	(Mechanical strength +Temperature	8	0.441		
	conditioned)	9	0.506		
	Department to at	10	0.415		
	Penetration test (As received)	11	0.753		
	(AS received)	12	0.816		
	Penetration test	13	0.756		
Paraffin oil test		14	0.573		
	(Simulated wearing treatment)	15	0.691		
	Exposure test	16	1.269		
	(Mechanical strength +Temperature	17	1.209		
	conditioned)	18	1.365		
Flow conditioning: Single filter: 95.0 L/min					



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rd Building, No. 889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52115295849201TX

Date: August 24,2021

Page 5 of 10

Clause 7.10 Compatibility with Skin

(EN 149:2001+A1:2009, Clause 8.4 & 8.5)

Test Requirement	Results	Comment
Materials that may come into contact with the wearer's skin shall not be known to be likely to cause irritation or any other adverse effect to health.	No irritation or any other adverse effect to health	Pass

Clause 7.11 Flammability

(EN 149:2001+A1:2009, Clause 8.6)

Test Requirement	Results	Comment
The material used shall not present a danger for the wearer and shall not be of highly flammable nature	Detail refer to	Pass
When tested, the particle filtering half mask shall not burn or not to continue to burn for more than 5 s after removal from the flame.	Appendix 3	1 433

Appendix 3: Summarization of Test Data

Flammability

Condition	Sample No.	Result
	1	NIL
As received	2	NIL
	3	NIL
Temperature conditioned	4	NIL

Clause 7.12 Carbon Dioxide Content of The Inhalation Air

(EN 149:2001+A1:2009, Clause 8.7)

Test Requirement	Results	Comment
The carbon dioxide content of the inhalation air (dead space) shall not	Detail refer to	Pass
exceed an average of 1,0 % (by volume)	Appendix 4	1 033

Appendix 4: Summarization of Test Data

Carbon Dioxide Content of The Inhalation Air

Condition	Sample No.	Res	sult
	1	0.5622	
As received	2	0.5638	Mean value:0.56
	3	0.5649	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐江区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 t (86-21) 61402666

f (86-21) 64958763 f (86-21) 64958763



SL52115295849201TX

Date: August 24,2021

Page 6 of 10

Clause 7.13 Head Harness

(EN 149:2001+A1:2009, Clause 8.4 & 8.5)

Test Requirement	Results	Comment
The head harness shall be designed so that the particle filtering half mask can be donned and removed easily.	Comply	
The head harness shall be adjustable or self-adjusting and shall be sufficiently robust to hold the particle filtering half mask firmly in position and be capable of maintaining total inward leakage requirements for the device.	Comply	Pass

Clause 7.14 Field of Vision

(EN 149:2001+A1:2009, Clause 8.4)

Test Requirement	Results	Comment
The field of vision is acceptable if determined so in practical performance	Comply	Pass
tests.	Comply	1 855

Clause 7.15 Exhalation Valve(s)

(EN 149:2001+A1:2009, Clause 8.2 & 8.9.1 & 8.3.4 & 8.8)

Test Requirement	Results	Comment
(a) A particle filtering half mask may have one or more exhalation valve(s), which shall function correctly in all orientations.	Not applicable due to No exhalation valve	
(b) If an exhalation valve is provided it shall be protected against or be resistant to dirt and mechanical damage and may be shrouded or may include any other device that may be necessary for the particle filtering half mask to comply with 7.9.	Not applicable due to No exhalation valve	N.A.
(c) Exhalation valve(s), if fitted, shall continue to operate correctly after a continuous exhalation flow of 300 l/min over a period of 30 s.	Not applicable due to No exhalation valve	
(d) When the exhalation valve housing is attached to the faceblank, it shall withstand axially a tensile force of 10N applied for 10 s.	Not applicable due to No exhalation valve	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rd Building, No. 889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52115295849201TX

Date: August 24,2021

Page 7 of 10

Clause 7.16 Breathing Resistance

(EN 149:2001+A1:2009, Clause 8.9)

	Tes	Results	Comment			
The breathing re half masks and s						
Classification	Maximu	um permitted resista	ance (mbar)		5 . "	Meet FFP1, Meet FFP2,
	Inf	nalation	Exhalation		Detail refer to	
	30 l/min	95 l/min	160 l/min		Appendix 5	Meet FFP3
FFP1	0.6	2.1	3.0			
FFP2	0.7	2.4	3.0			
FFP3	1.0	3.0	3.0			

Appendix 5: Summarization of Test Data

Breathing resistance (mbar)

								_					_				
	Class rate/L	/min)			1			2					3				
	Flow rate(I/	TIIIII)	Α	В	C	D	Е	Α	В	С	D	Е	Α	В	С	D	E
As received	Inhalation	30	0.4	0.5	0.4	0.4	0.4	0.4	0.4	0.5	0.5	0.4	0.4	0.4	0.4	0.5	0.5
	IIIIaiatioii	95	1.5	1.6	1.6	1.6	1.5	1.5	1.5	1.6	1.6	1.6	1.6	1.6	1.5	1.5	1.5
	Exhalation	160	2.1	2.0	2.0	2.0	2.1	2.1	2.1	2.1	2.1	2.0	2.0	2.0	2.1	2.1	2.1
	5 1 (1/1)				4					5			6				
Simulated	Flow rate(I/	min)	Α	В	C	D	Е	Α	В	С	D	Е	Α	В	С	D	Е
wearing	Inhalation	30	0.5	0.5	0.4	0.4	0.4	0.4	0.4	0.4	0.5	0.5	0.5	0.4	0.4	0.4	0.5
treatment	IIIIaiation	95	1.5	1.5	1.6	1.6	1.6	1.6	1.5	1.5	1.5	1.6	1.6	1.6	1.6	1.5	1.5
	Exhalation	160	2.0	2.1	2.1	2.1	2.0	2.0	2.0	2.1	2.1	2.1	2.0	2.0	2.0	2.1	2.1
	El	/··			7			8				9					
	Flow rate(I/	min)	Α	В	O	D	Е	Α	В	С	D	Е	Α	В	С	D	Е
Temperature	Inhalation	30	0.4	0.4	0.5	0.5	0.4	0.4	0.4	0.4	0.4	0.5	0.5	0.5	0.4	0.4	0.4
conditioned	IIIIIaialiOII	95	1.6	1.5	1.5	1.5	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.5	1.5	1.5	1.6
	Exhalation	160	2.0	2.0	2.1	2.1	2.1	2.1	2.1	2.0	2.0	2.0	2.1	2.1	2.0	2.0	2.1

A: facing directly ahead; B: facing vertically upwards; C: facing vertically downwards; D: lying on the left side; E: lying on the right side



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐江区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 t (86-21) 61402666

f (86-21) 64958763 f (86-21) 64958763



SL52115295849201TX

Date: August 24,2021

Page 8 of 10

Clause 7.17 Clogging

(EN 149:2001+A1:2009, Clause 8.9 & 8.10)

	Test Requirement	Results	Comment	
Valved particle file After clogging the FFP1: 4 mbar, File The exhalation re flow. Valveless particle After clogging the	eathing resistance Itering half masks: e inhalation resistances shall not FP2: 5 mbar, FFP3: 7 mbar at 95 esistance shall not exceed 3 mb e filtering half masks: e inhalation and exhalation resis	5L/min continuous flow par at 160 L/min continuous tances shall not exceed:	Optional for single shift device only	N.A.
FFF1. 3 IIIbai, F	FP2: 4 mbar, FFP3: 5 mbar at 95	DL/IIIII COIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII		
All types (valved meet the cloggin	enetration of filter material I and valveless) of particle filte g requirement shall also meet th	e requirements.		
All types (valved meet the cloggin	d and valveless) of particle filte g requirement shall also meet th Maximum penetration	n of test aerosol		
All types (valved meet the cloggin	d and valveless) of particle filte g requirement shall also meet th	n of test aerosol	Optional for single	N.A.
All types (valved meet the cloggin	d and valveless) of particle filte g requirement shall also meet th Maximum penetration	n of test aerosol	Optional for single shift device only	N.A.
All types (valved meet the cloggin	d and valveless) of particle filte g requirement shall also meet th Maximum penetration Sodium chloride test 95 l/min	n of test aerosol Paraffin oil test 95 l/min		N.A.
All types (valved meet the cloggin	d and valveless) of particle filte g requirement shall also meet th Maximum penetration Sodium chloride test 95 l/min	n of test aerosol Paraffin oil test 95 l/min %		N.A.
All types (valved meet the cloggin Classificatio n	d and valveless) of particle filte g requirement shall also meet th Maximum penetration Sodium chloride test 95 l/min % max.	n of test aerosol Paraffin oil test 95 l/min % max.		N.A.

Clause 7.18 Demountable Parts

(EN 149:2001+A1:2009, Clause 8.2)

Test Requirement	Results	Comment
All demountable parts (if fitted) shall be readily connected and secured, where possible by hand	No demountable parts	N.A.

Test	Uncertainty
Total inward leakage	3.4%
Penetration of filter material	4.8%
Carbon dioxide content of the inhalation air	3.9%
Breathing resistance (30L/min)	5.9%
Breathing resistance (95L/min)	4.9%
Breathing resistance (160L/min)	4.3%



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rd Building, No. 889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763




SL52115295849201TX

Date: August 24,2021

Page 9 of 10

Sample Photo





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rd Building, No. 889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666


t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52115295849201TX

Date: August 24,2021

Page 10 of 10



Product information is provided by applicant without verification of authentication of the brand.

End of Report



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐江区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 t (86-21) 61402666

f (86–21) 64958763 f (86–21) 64958763